


L4CLAMP-CNL-E4B



KwikClamp™ Hanger for 1/2 in coaxial cable, triple stack, C-Channel compatible; includes hardware

Product Classification

Product Type	Hanger kit
Product Brand	KwikClamp™
Ordering Note	ANDREW® standard product in Europe, the Middle East, and Africa Minimum order quantity (MOQ) is 1 box

General Specifications

Cables per Hanger	4
Color	Black
Hanger Type	KwikClamp™ hanger
Mounting	Channel section 40 x 22 x 1.5 mm

Dimensions

Height	197 mm 7.756 in
Width	32 mm 1.26 in
Length	42 mm 1.654 in
Compatible Diameter, maximum	17 mm 0.669 in
Compatible Diameter, minimum	15 mm 0.591 in
Nominal Size	1/2 in
Hanger Spacing, maximum	1.83 m 6.004 ft

Electrical Specifications

Return Loss Effect, maximum	0.1 dB
DTF Effect, maximum	0.1 dB

Material Specifications

Material Type	Engineered plastic Stainless steel
---------------	--------------------------------------

Mechanical Specifications

L4CLAMP-CNL-E4B

Vibration Survival	≥4 hours at resonant frequency
Environmental Specifications	
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Corrosion Resistance, minimum with no degradation	≥500 hours in salt spray chamber
Environmental Strength Capability	Five times cable weight
UV Resistance, minimum with no degradation	≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed	32.8 cm 12.913 in
Width, packed	30.5 cm 12.008 in
Length, packed	20 cm 7.874 in
Included	Hardware
Packaging quantity	100
Weight, gross	17 kg 37.479 lb