


L5CLAMP-CNL-E4B



KwikClamp™ Hanger for 7/8 in coaxial cable, triple stack, C-Channel compatible; includes hardware

Product Classification

Product Type	Hanger kit
Product Brand	KwikClamp™
Ordering Note	ANDREW® standard product in Europe, the Middle East, and Africa Minimum order quantity (MOQ) is 1 box

General Specifications

Cables per Hanger	4
Color	Black
Hanger Type	KwikClamp™ hanger
Mounting	Channel section 40 x 22 x 1.5 mm

Dimensions

Height	235 mm 9.252 in
Width	45 mm 1.772 in
Length	32 mm 1.26 in
Compatible Diameter, maximum	28 mm 1.102 in
Compatible Diameter, minimum	26 mm 1.024 in
Nominal Size	7/8 in
Hanger Spacing, maximum	1.83 m 6.004 ft

Electrical Specifications

Return Loss Effect, maximum	0.1 dB
DTF Effect, maximum	0.1 dB

Material Specifications

Material Type	Engineered plastic Stainless steel
---------------	--------------------------------------

Mechanical Specifications

L5CLAMP-CNL-E4B

Vibration Survival	≥4 hours at resonant frequency
Environmental Specifications	
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Corrosion Resistance, minimum with no degradation	≥500 hours in salt spray chamber
Environmental Strength Capability	Five times cable weight
UV Resistance, minimum with no degradation	≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed	33 cm 12.992 in
Width, packed	22 cm 8.661 in
Length, packed	27 cm 10.63 in
Included	Hardware
Packaging quantity	100
Weight, gross	30 kg 66.139 lb