


# HX12-4-4GR



3.6m | 12ft ValuLine® High Performance, High XPD Antenna, dual-polarized, 4.400 – 5.000 GHz, grey, PDR48 flange

## Product Classification

**Product Type** Microwave antenna

## General Specifications

|                               |                                                                   |
|-------------------------------|-------------------------------------------------------------------|
| <b>Antenna Type</b>           | HX - ValuLine® High Performance, High XPD Antenna, dual-polarized |
| <b>Polarization</b>           | Dual                                                              |
| <b>Antenna Input</b>          | PDR48                                                             |
| <b>Antenna Color</b>          | Gray                                                              |
| <b>Reflector Construction</b> | Two-piece reflector                                               |
| <b>Radome Color</b>           | Gray                                                              |
| <b>Radome Material</b>        | Fabric                                                            |
| <b>Flash Included</b>         | No                                                                |
| <b>Side Struts, Included</b>  | 2                                                                 |

## Dimensions

**Diameter, nominal** 3.6 m | 12 ft

## Electrical Specifications

|                                                         |                   |
|---------------------------------------------------------|-------------------|
| <b>Operating Frequency Band</b>                         | 4.400 – 5.000 GHz |
| <b>Gain, Low Band</b>                                   | 41.6 dBi          |
| <b>Gain, Mid Band</b>                                   | 42.2 dBi          |
| <b>Gain, Top Band</b>                                   | 42.7 dBi          |
| <b>Boresite Cross Polarization Discrimination (XPD)</b> | 33 dB             |
| <b>Front-to-Back Ratio</b>                              | 68 dB             |
| <b>Beamwidth, Horizontal</b>                            | 1.2 °             |
| <b>Beamwidth, Vertical</b>                              | 1.2 °             |
| <b>Return Loss</b>                                      | 21 dB             |

# HX12-4-4GR

---


|                                                                      |                               |
|----------------------------------------------------------------------|-------------------------------|
| <b>VSWR</b>                                                          | 1.15                          |
| <b>Radiation Pattern Envelope Reference (RPE)</b>                    | 7428                          |
| <b>Electrical Compliance</b>                                         | ETSI 302 217 Class 3          |
| <b>Cross Polarization Discrimination (XPD) Electrical Compliance</b> | ETSI EN 302217 XPD Category 2 |

## Mechanical Specifications

|                                          |                        |
|------------------------------------------|------------------------|
| <b>Compatible Mounting Pipe Diameter</b> | 115 mm   4.5 in        |
| <b>Fine Azimuth Adjustment Range</b>     | ±5°                    |
| <b>Fine Elevation Adjustment Range</b>   | ±5°                    |
| <b>Wind Speed, operational</b>           | 180 km/h   111.847 mph |
| <b>Wind Speed, survival</b>              | 200 km/h   124.274 mph |

# HX12-4-4GR

## Antenna Dimensions and Mounting Information




## Wind Forces at Wind Velocity Survival Rating

|                                       |                                 |
|---------------------------------------|---------------------------------|
| Axial Force (FA)                      | 26750 N   6,013.641 lbf         |
| Angle α for MT Max                    | -120 °                          |
| Side Force (FS)                       | 9450 N   2,124.445 lbf          |
| Twisting Moment (MT)                  | -17550 N-m   -155,330.594 in lb |
| Force on Inboard Strut Side           | 13000 N   2,922.517 lbf         |
| Force on Outboard Strut Side          | 4500 N   1,011.64 lbf           |
| Zcg without Ice                       | 680 mm   26.772 in              |
| Zcg with 1/2 in (12 mm) Radial Ice    | 841 mm   33.11 in               |
| Weight with 1/2 in (12 mm) Radial Ice | 643 kg   1,417.571 lb           |

# HX12-4-4GR

## Wind Forces at Wind Velocity Survival Rating Image



## Packaging and Weights

|                |                       |
|----------------|-----------------------|
| Height, packed | 1530 mm   60.236 in   |
| Width, packed  | 2140 mm   84.252 in   |
| Length, packed | 3990 mm   157.087 in  |
| Packaging Type | Standard pack         |
| Volume         | 13 m³   459.091 ft³   |
| Weight, gross  | 648 kg   1,428.594 lb |
| Weight, net    | 348 kg   767.208 lb   |

## Regulatory Compliance/Certifications

| Agency        | Classification                                                                                                           |
|---------------|--------------------------------------------------------------------------------------------------------------------------|
| CHINA-ROHS    | Above maximum concentration value                                                                                        |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system                                           |
| REACH-SVHC    | Compliant as per SVHC revision on <a href="http://www.andrew.com/ProductCompliance">www.andrew.com/ProductCompliance</a> |
| ROHS          | Compliant/Exempted                                                                                                       |
| UK-ROHS       | Compliant/Exempted                                                                                                       |



## \* Footnotes

|                          |                                                                                                                                                                                    |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Frequency Band | Bands correspond with CCIR recommendations or common allocations used throughout the world. Other ranges can be accommodated on special order.                                     |
| Gain, Mid Band           | For a given frequency band, gain is primarily a function of antenna size. The gain of Andrew antennas is determined by either gain by comparison or by computer integration of the |

**Boresite Cross Polarization Discrimination (XPD)**

measured antenna patterns.

The difference between the peak of the co-polarized main beam and the maximum cross-polarized signal over an angle twice the 3 dB beamwidth of the co-polarized main beam.

**Front-to-Back Ratio**

Denotes highest radiation relative to the main beam, at  $180^\circ \pm 40^\circ$ , across the band. Production antennas do not exceed rated values by more than 2 dB unless stated otherwise.

**Return Loss**

The figure that indicates the proportion of radio waves incident upon the antenna that are rejected as a ratio of those that are accepted.

**VSWR**

Maximum; is the guaranteed Peak Voltage-Standing-Wave-Ratio within the operating band.

**Radiation Pattern Envelope Reference (RPE)**

Radiation patterns define an antenna's ability to discriminate against unwanted signals. Under still dry conditions, production antennas will not have any peak exceeding the current RPE by more than 3dB, maintaining an angular accuracy of  $\pm 1^\circ$  throughout

**Cross Polarization Discrimination (XPD) Electrical Compliance**

The difference between the peak of the co-polarized main beam and the maximum cross-polarized signal over an angle twice the 3 dB beamwidth of the co-polarized main beam.

**Wind Speed, operational**

For VHLP(X), SHP(X), HX and USX antennas, the wind speed where the maximum antenna deflection is  $0.3 \times$  the 3 dB beam width of the antenna. For other antennas, it is defined as a deflection is equal to or less than 0.1 degrees.

**Wind Speed, survival**

The maximum wind speed the antenna, including mounts and radomes, where applicable, will withstand without permanent deformation. Realignment may be required. This wind speed is applicable to antenna with the specified amount of radial ice.

**Axial Force (FA)**

Maximum forces exerted on a supporting structure as a result of wind from the most critical direction for this parameter. The individual maximums specified may not occur simultaneously. All forces are referenced to the mounting pipe.

**Side Force (FS)**

Maximum side force exerted on the mounting pipe as a result of wind from the most critical direction for this parameter. The individual maximums specified may not occur simultaneously. All forces are referenced to the mounting pipe.

**Twisting Moment (MT)**

Maximum forces exerted on a supporting structure as a

# HX12-4-4GR

---

result of wind from the most critical direction for this parameter. The individual maximums specified may not occur simultaneously. All forces are referenced to the mounting pipe.

## **Packaging Type**

Andrew standard packing is suitable for export. Antennas are shipped as standard in totally recyclable cardboard or wire-bound crates (dependent on product). For your convenience, Andrew offers heavy duty export packing options.