

29961



Lace-up Hoisting Grip for HELIAX® 1.37-1.77 in (35-45 mm) cables and elliptical waveguide 64

Product Classification

| | |
|----------------------|------------------------------|
| Product Type | Hoisting grip |
| Product Brand | HELIAX® |
| Ordering Note | ANDREW® non-standard product |

General Specifications

| | |
|-------------------------------------|-----------------------|
| Attachment Spacing Intervals | 60.96 m 200 ft |
| Hoisting Grip Type | Lace-up hoisting grip |
| Support Clamp | Not included |
| Tool Type | Hoisting grip |

Dimensions

| | |
|-------------------------------------|------------------|
| Grip Length, minimum | 635 mm 25 in |
| Leader Length, minimum | 203.2 mm 8 in |
| Compatible Diameter, maximum | 45 mm 1.772 in |
| Compatible Diameter, minimum | 35 mm 1.378 in |
| Nominal Size | 1-1/4 in |

Electrical Specifications

| | |
|------------------------------------|--------|
| Return Loss Effect, maximum | 0.1 dB |
| DTF Effect, maximum | 0.1 dB |

Material Specifications

| | |
|----------------------|-----------------|
| Material Type | Stainless steel |
|----------------------|-----------------|

Mechanical Specifications

| | |
|---------------------------|---------------------|
| Pull Load Capacity | 408.233 kg 900 lb |
|---------------------------|---------------------|

29961

Packaging and Weights

| | |
|---------------------------|--------------------|
| Height, packed | 55.88 mm 2.2 in |
| Width, packed | 236.22 mm 9.3 in |
| Length, packed | 236.22 mm 9.3 in |
| Packaging quantity | 1 |
| Weight, gross | 0.38 kg 0.838 lb |

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| CHINA-ROHS | Below maximum concentration value |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| REACH-SVHC | Compliant as per SVHC revision on www.andrew.com/ProductCompliance |
| ROHS | Compliant |
| UK-ROHS | Compliant |

