

# L4CLAMP-CNL-2B



KwikClamp™ Hanger for 1/2 in coaxial cable, double stack, C-Channel compatible; includes hardware

## Product Classification

|               |                                                                                                         |
|---------------|---------------------------------------------------------------------------------------------------------|
| Product Type  | Hanger kit                                                                                              |
| Product Brand | KwikClamp™                                                                                              |
| Ordering Note | ANDREW® standard product in Europe, the Middle East, and Africa   Minimum order quantity (MOQ) is 1 box |

## General Specifications

|                   |                                  |
|-------------------|----------------------------------|
| Cables per Hanger | 2                                |
| Color             | Black                            |
| Hanger Type       | KwikClamp™ hanger                |
| Mounting          | Channel section 40 x 22 x 1.5 mm |

## Dimensions

|                              |                   |
|------------------------------|-------------------|
| Height                       | 143 mm   5.63 in  |
| Width                        | 32 mm   1.26 in   |
| Length                       | 42 mm   1.654 in  |
| Compatible Diameter, maximum | 17 mm   0.669 in  |
| Compatible Diameter, minimum | 15 mm   0.591 in  |
| Nominal Size                 | 1/2 in            |
| Hanger Spacing, maximum      | 1.83 m   6.004 ft |

## Electrical Specifications

|                             |        |
|-----------------------------|--------|
| Return Loss Effect, maximum | 0.1 dB |
| DTF Effect, maximum         | 0.1 dB |

## Material Specifications

|               |                                      |
|---------------|--------------------------------------|
| Material Type | Engineered plastic   Stainless steel |
|---------------|--------------------------------------|

## Mechanical Specifications

# L4CLAMP-CNLC-2B

---

|                                                          |                                                    |
|----------------------------------------------------------|----------------------------------------------------|
| <b>Vibration Survival</b>                                | ≥4 hours at resonant frequency                     |
| <b>Environmental Specifications</b>                      |                                                    |
| <b>Operating Temperature</b>                             | -40 °C to +70 °C (-40 °F to +158 °F)               |
| <b>Corrosion Resistance, minimum with no degradation</b> | ≥500 hours in salt spray chamber                   |
| <b>Environmental Strength Capability</b>                 | Five times cable weight                            |
| <b>UV Resistance, minimum with no degradation</b>        | ≥100 hours exposure in accelerated UV life chamber |

## Packaging and Weights

|                           |                     |
|---------------------------|---------------------|
| <b>Height, packed</b>     | 32.8 cm   12.913 in |
| <b>Width, packed</b>      | 30.5 cm   12.008 in |
| <b>Length, packed</b>     | 20 cm   7.874 in    |
| <b>Included</b>           | Hardware            |
| <b>Packaging quantity</b> | 100                 |
| <b>Weight, gross</b>      | 10 kg   22.046 lb   |