

L7CLAMP-CNL-1B



KwikClamp™ Hanger for 1-5/8 in coaxial cable, single stack, C-Channel compatible; includes hardware

Product Classification

Product Type	Hanger kit
Product Brand	KwikClamp™
Ordering Note	ANDREW® standard product in Europe, the Middle East, and Africa Minimum order quantity (MOQ) is 1 box

General Specifications

Cables per Hanger	1
Color	Black
Hanger Type	KwikClamp™ hanger
Mounting	Channel section 40 x 22 x 1.5 mm

Dimensions

Height	152 mm 5.984 in
Width	69 mm 2.717 in
Length	44 mm 1.732 in
Compatible Diameter, maximum	50 mm 1.969 in
Compatible Diameter, minimum	48 mm 1.89 in
Nominal Size	1-5/8 in
Hanger Spacing, maximum	1.83 m 6.004 ft

Electrical Specifications

Return Loss Effect, maximum	0.1 dB
DTF Effect, maximum	0.1 dB

Material Specifications

Material Type	Engineered plastic Stainless steel
---------------	--------------------------------------

Mechanical Specifications

L7CLAMP-CN1-1B

Vibration Survival	≥4 hours at resonant frequency
Environmental Specifications	
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Corrosion Resistance, minimum with no degradation	≥500 hours in salt spray chamber
Environmental Strength Capability	Five times cable weight
UV Resistance, minimum with no degradation	≥100 hours exposure in accelerated UV life chamber
Packaging and Weights	
Height, packed	101 cm 39.764 in
Width, packed	71 cm 27.953 in
Length, packed	81.3 cm 32.008 in
Included	Hardware
Packaging quantity	100
Weight, gross	17 kg 37.479 lb