

# L7CLAMP-CNL-3B



KwikClamp™ Hanger for 1-5/8 in coaxial cable, triple stack, C-Channel compatible; includes hardware

## Product Classification

|               |                                                                                                         |
|---------------|---------------------------------------------------------------------------------------------------------|
| Product Type  | Hanger kit                                                                                              |
| Product Brand | KwikClamp™                                                                                              |
| Ordering Note | ANDREW® standard product in Europe, the Middle East, and Africa   Minimum order quantity (MOQ) is 1 box |

## General Specifications

|                   |                                  |
|-------------------|----------------------------------|
| Cables per Hanger | 3                                |
| Color             | Black                            |
| Hanger Type       | KwikClamp™ hanger                |
| Mounting          | Channel section 40 x 22 x 1.5 mm |

## Dimensions

|                              |                    |
|------------------------------|--------------------|
| Height                       | 282 mm   11.102 in |
| Width                        | 69 mm   2.717 in   |
| Length                       | 44 mm   1.732 in   |
| Compatible Diameter, maximum | 50 mm   1.969 in   |
| Compatible Diameter, minimum | 48 mm   1.89 in    |
| Nominal Size                 | 1-5/8 in           |
| Hanger Spacing, maximum      | 1.83 m   6.004 ft  |

## Electrical Specifications

|                             |        |
|-----------------------------|--------|
| Return Loss Effect, maximum | 0.1 dB |
| DTF Effect, maximum         | 0.1 dB |

## Material Specifications

|               |                                      |
|---------------|--------------------------------------|
| Material Type | Engineered plastic   Stainless steel |
|---------------|--------------------------------------|

## Mechanical Specifications

# L7CLAMP-CNL-3B

---

|                                                   |                                                    |
|---------------------------------------------------|----------------------------------------------------|
| Vibration Survival                                | ≥4 hours at resonant frequency                     |
| Environmental Specifications                      |                                                    |
| Operating Temperature                             | -40 °C to +70 °C (-40 °F to +158 °F)               |
| Corrosion Resistance, minimum with no degradation | ≥500 hours in salt spray chamber                   |
| Environmental Strength Capability                 | Five times cable weight                            |
| UV Resistance, minimum with no degradation        | ≥100 hours exposure in accelerated UV life chamber |
| Packaging and Weights                             |                                                    |
| Height, packed                                    | 101 cm   39.764 in                                 |
| Width, packed                                     | 71 cm   27.953 in                                  |
| Length, packed                                    | 81.3 cm   32.008 in                                |
| Included                                          | Hardware                                           |
| Packaging quantity                                | 100                                                |
| Weight, gross                                     | 38 kg   83.776 lb                                  |