

# L6-CLAMP-2B



KwikClamp™ Hanger for 1-1/4 in coaxial cable, double stack; includes hardware

## Product Classification

|               |                                                                                                         |
|---------------|---------------------------------------------------------------------------------------------------------|
| Product Type  | Hanger kit                                                                                              |
| Product Brand | KwikClamp™                                                                                              |
| Ordering Note | ANDREW® standard product in Europe, the Middle East, and Africa   Minimum order quantity (MOQ) is 1 box |

## General Specifications

|                   |                                                                |
|-------------------|----------------------------------------------------------------|
| Cables per Hanger | 2                                                              |
| Color             | Black                                                          |
| Hanger Type       | KwikClamp™ hanger                                              |
| Mounting          | 3–25 mm angle iron   3–25 mm flat plate   Round Member 8-25 mm |

## Dimensions

|                              |                   |
|------------------------------|-------------------|
| Height                       | 192 mm   7.559 in |
| Width                        | 57 mm   2.244 in  |
| Length                       | 45 mm   1.772 in  |
| Compatible Diameter, maximum | 40 mm   1.575 in  |
| Compatible Diameter, minimum | 38 mm   1.496 in  |
| Nominal Size                 | 1-1/4 in          |
| Hanger Spacing, maximum      | 1.83 m   6.004 ft |

## Electrical Specifications

|                             |        |
|-----------------------------|--------|
| Return Loss Effect, maximum | 0.1 dB |
| DTF Effect, maximum         | 0.1 dB |

## Material Specifications

|               |                                      |
|---------------|--------------------------------------|
| Material Type | Engineered plastic   Stainless steel |
|---------------|--------------------------------------|

# L6-CLAMP-2B

## Mechanical Specifications

**Vibration Survival** ≥4 hours at resonant frequency

## Environmental Specifications

**Operating Temperature** -40 °C to +70 °C (-40 °F to +158 °F)

**Corrosion Resistance, minimum with no degradation** ≥500 hours in salt spray chamber

**Environmental Strength Capability** Five times cable weight

**UV Resistance, minimum with no degradation** ≥100 hours exposure in accelerated UV life chamber

## Packaging and Weights

**Height, packed** 15.5 cm | 6.102 in

**Width, packed** 30.5 cm | 12.008 in

**Length, packed** 35.5 cm | 13.976 in

**Included** Hardware

**Packaging quantity** 30

**Weight, gross** 7.8 kg | 17.196 lb

## Regulatory Compliance/Certifications

| Agency     | Classification                                                                                                           |
|------------|--------------------------------------------------------------------------------------------------------------------------|
| CHINA-ROHS | Below maximum concentration value                                                                                        |
| REACH-SVHC | Compliant as per SVHC revision on <a href="http://www.andrew.com/ProductCompliance">www.andrew.com/ProductCompliance</a> |
| ROHS       | Compliant                                                                                                                |
| UK-ROHS    | Compliant                                                                                                                |

