

# F-CLAMP-E2-3B



KwikClamp™ Hanger for power & fiber cables, two 9-12 mm holes (alongside each other), triple block; includes hardware

## Product Classification

|               |                                                                                                         |
|---------------|---------------------------------------------------------------------------------------------------------|
| Product Type  | Hanger kit                                                                                              |
| Product Brand | KwikClamp™                                                                                              |
| Ordering Note | ANDREW® standard product in Europe, the Middle East, and Africa   Minimum order quantity (MOQ) is 1 box |

## General Specifications

|                   |                                                                |
|-------------------|----------------------------------------------------------------|
| Cables per Hanger | 3                                                              |
| Color             | Black                                                          |
| Hanger Type       | KwikClamp™ hanger                                              |
| Mounting          | 3–25 mm angle iron   3–25 mm flat plate   Round Member 8-25 mm |

## Dimensions

|                                 |                   |
|---------------------------------|-------------------|
| Height                          | 158 mm   6.22 in  |
| Width                           | 44 mm   1.732 in  |
| Length                          | 42 mm   1.654 in  |
| Compatible Cable Diameter Range | 9–12 mm           |
| Compatible Diameter, maximum    | 12 mm   0.472 in  |
| Compatible Diameter, minimum    | 9 mm   0.354 in   |
| Hanger Spacing, maximum         | 1.83 m   6.004 ft |

## Electrical Specifications

|                             |        |
|-----------------------------|--------|
| Return Loss Effect, maximum | 0.1 dB |
| DTF Effect, maximum         | 0.1 dB |

## Material Specifications

|               |                                      |
|---------------|--------------------------------------|
| Material Type | Engineered plastic   Stainless steel |
|---------------|--------------------------------------|

# F-CLAMP-E2-3B

---

## Mechanical Specifications

**Vibration Survival** ≥4 hours at resonant frequency

## Environmental Specifications

**Operating Temperature** -40 °C to +70 °C (-40 °F to +158 °F)

**Corrosion Resistance, minimum with no degradation** ≥500 hours in salt spray chamber

**Environmental Strength Capability** Five times cable weight

**UV Resistance, minimum with no degradation** ≥124 hours exposure in accelerated UV life chamber, testing duration 1344 hrs

## Packaging and Weights

**Height, packed** 15.5 cm | 6.102 in

**Width, packed** 30.5 cm | 12.008 in

**Length, packed** 35.5 cm | 13.976 in

**Included** Hardware

**Packaging quantity** 42

**Weight, gross** 8.7 kg | 19.18 lb